



REMOVABLE
MOD. B4-5B2-R

FIXED
MOD. B4-5B2

SPECIFICATIONS:

1. MATERIAL: 5" SCH. 10 STEEL PIPE - ASTM A53.
2. GROUND RECEIVER: 10 GAUGE STEEL SLEEVE (REMOVABLE BOLLARD) WELDED TO A 3"x5" LOCKWELL. BASE SHALL BE SET IN CONCRETE 24" DEEP. CONCRETE SHALL BE MIN. 6" THICK AROUND RECEIVER SLEEVE.
3. COATING: 3 - 4 MILS THICK BLACK POWDER COATING
4. HEIGHT: 36 INCHES
5. TOP STYLE: DOME
6. MANUFACTURER: BOLLARDS SHALL BE MODEL B4-5B2-R (REMOVABLE) AND B4-5B2 (FIXED) BY FAIRWEATHER SITE FURNISHINGS PORT ORCHARD, WA OR APPROVED EQUAL.

NOTES:

THIS STANDARD SHALL APPLY TO:
TRAIL DEVELOPMENT NORTH OF 164TH ST. SE, WEST OF SR527,
SOUTH OF MCCOLLUM PARK AND EAST OF NORTH CREEK.



STANDARD PLANS
BOLLARDS

STR 063

APPROVED: *Douglas Johnson*
Director of Public Works/City Engineer

REVISION: FEB 2003 NOT TO SCALE BY: L.C.